



LOG-GEVITY™ WATERBORNE URETHANE PRODUCT SPECIFICATIONS

PRODUCT NAME

Log-Gevity™ Waterborne Urethane

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
U.S.A.
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Log-Gevity™ Waterborne Urethane is a scratch and nick resistant durable finish, recommended for interior wood floors, doors, paneling and wood trim. Log-Gevity™ Waterborne Urethane forms a protective coating resistant to abrasive foot traffic and other destructive elements. Log-Gevity™ Waterborne Urethane is available in both gloss and semi-gloss.

Precautions: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces including vegetation. Beware of wind drift onto auto and pedestrian traffic.

TECHNICAL DATA

Color/Form: Clear liquid.

Packaging: One gallon containers.

VOC Content Limit: 400 grams per liter.

Coverage:

Wood Floor: 400 to 500 sq. ft. per gallon.

Other surfaces: 250 to 500 sq. ft. per gallon subject to porosity.

PROPER SURFACE PREPARATION

A test area should be performed in an inconspicuous area prior to beginning overall project to determine compatibility.

User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

Old Floor: Surface should be free from wax and oil. Abrade with medium steel wool pad. Log-Gevity™ Waterborne Urethane will adhere to most stains and finishes.

New Floor: Sand floor with a fine grit sand paper. For a natural wood floor finish lightly sand with 100 grit paper. The purpose of sanding is to reduce the amount of raised grain. Vacuum excess residue, then use water dampened cloth to clean dust particles.

GENERAL DIRECTIONS

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Wood Floor Application:

1. **Do not shake container.** Thoroughly stir Log-Gevity™ Waterborne Urethane slowly to avoid air bubbles before using.

2. Pour Log-Gevity™ Waterborne Urethane onto the surface. Use paint pad and draw with the grain. **Do not use a roller or paint brush.**

Note: Excess brushing will cause product to bubble.

For best results: Slowly draw with painter's pad.

3. Feather out all turns. To prevent lapping and dry marks, use the spread ratio coverage of 400 - 500 sq. ft. per gallon. Allow first and second (if desired third) coat to dry a minimum of 2 - 3 hours. Allow 48 hours for final coat to dry before use.

For best results and smoothest floor: Sand lightly with 220 grit between all coats. After sanding, use water dampened cloth to clean dust particles.

Other Surface Application:

(Such as Doors, paneling, wood trim and logs.)

1. **Do not shake container.** Thoroughly stir Log-Gevity™ Waterborne Urethane slowly before using to avoid air bubbles.
2. Two coats are recommended, allowing 2-3 hours between applications.

For best results and smooth wood: Sand lightly with 220 grit between 1st and 2nd coat for a smooth finish. After sanding, use water dampened cloth to clean dust particles.

CLEAN UP: Immediately clean tools with soap and water.

MAINTENANCE: Do not clean floor or other surface with any type of detergent or cleaner during first week after completion. Wipe floor/surface with water dampened cloth.

DRY TIME: Floor will accept normal traffic after 24 hours. However the floor is susceptible to scuffing and scratching. Total cure time is approximately seven days. **Do not replace area rugs until floor has cured for seven days.**

SHELF LIFE: One year in an opened container.

AVAILABILITY

Available through a network of distributors, dealers and representatives.

NOTICE: the information and recommendations made herein are based on **ABRP, Inc.**, research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because **ABRP, Inc.**, cannot anticipate every possible application of **ABRP, Inc.**, products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of **ABRP, Inc.**, products are not intended

as recommendation to use **ABRP, Inc.**, products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed or implied, including without limitation warranties as to **MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.**

This limited warranty may not be modified or extended by

manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to the purchaser. This warranty gives the purchaser specific legal rights, as well as, other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs a manufacturer-direct personal assistance staff and field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications and brochures are available upon request.

Visit www.Log-Gevity.com for additional information regarding log home restoration and preservation products.

For more information on many of the specialty building restoration products available from **ABRP, Inc.**, please visit www.abrp.com or e-mail **ABRP, Inc.** at support@abrp.com.

© Copyright 2005 ABR Products, Inc.